

TACTICAL

T-SERIES

GERMAN
PRECISION.
AMERICAN
MADE.



THE T6XI RIFLESCOPES
SERIES OFFERS,
THE ULTIMATE IN
PRECISION,
RUGGEDNESS AND
VERSATILITY.



T6Xi 5-30X56

The T6Xi riflescopes feature a diopter locking ring that ensures it cannot be moved once the reticle is focused on the users eye.

TUBE DIAMETER 34 MM | LENGTH 15.75 IN. | BATTERY CR2450
ITEM NO. 5124 (MSR2 - MIL) | UPC 000381851246
ITEM NO. 5125 (SCR2-MIL) | UPC 000381851253

T-SERIES OVERALL FEATURES

- 6X ZOOM RANGE
- LOCKING WINDAGE AND ELEVATION TURRETS
- LOW-PROFILE NEVER-LOST™ TURRETS
- SECOND ROTATION INDICATOR
- ILLUMINATION - 2 NV
4 NIGHT - 5 DAY
- WATERPROOF/ FOGPROOF/
SHOCKPROOF

Steiner offers a selection of reticles in the T6Xi line of riflescopes. For more information on these reticle designs, refer steiner-optics.com



T6Xi 3-18X56

TUBE DIAMETER 34 MM | LENGTH 13.6 IN. | BATTERY CR2450
ITEM NO. 5118 (MSR2 - MIL) | UPC 000381851185
ITEM NO. 5119 (SCR) | UPC 000381851192

Windage and elevation feature locking turrets and are indicated by detents and audible clicks.



T6Xi 2.5-15X50

TUBE DIAMETER 34 MM | LENGTH 12.8 IN. | BATTERY CR2450
ITEM NO. 5116 (SCR™ - MIL) | UPC 000381851161
ITEM NO. 5117 (SCR) | UPC 000381851178

1-6x24mm models come with both exposed and capped elevation turrets for user preference. And includes the Steiner proprietary KC-1 reticle developed in partnership with John Dufrense at Kinetic Consulting.




T6Xi 1-6X24

TUBE DIAMETER 30 MM | LENGTH 10.4 IN. | BATTERY CR2450
ITEM NO. 5103 (KC-1 MIL) | UPC 000381851031




HERITAGE
WARRANTY
GENERATION
TO GENERATION






1x


KC1 RETICLE




6x



MSR2 - MIL



SCR™



SCR2 - MIL

SPECIFICATIONS

	1-6x24	2.5-15x50	3-18x56	5-30x56
ITEM NUMBER	5103	5116 / 5117	5118 / 5119	5124 / 5125
MAGNIFICATION	1-6x	2.5-15x	3-18x	5-30x
OBJECTIVE LENS DIA.(mm)	24	50	56	56
TUBE DIAMETER (mm)	30	34	34	34
FOCAL PLANE	1st	1st	1st	1st
FIELD OF VIEW (ft @ 100 yd) LOW/HIGH	114 - 19	44.5 - 8.5	37 - 7	22 - 4
EYE RELIEF (in) LOW/HIGH	3.9-3.4	3.5-3.3	3.5-3.3	3.5-3.3
EXIT PUPIL (mm) LOW/HIGH	10.3 - 4.0	9.7 - 3.4	9.7 - 3.2	9.7 - 1.8
LENGTH (in)	10.4	12.8	13.6	15.75
WEIGHT (oz)	20	32	34.4	34.5
DIOPTRER ADJUSTMENT RANGE	+2 to -3	+2 to -3	+2 to -3	+2 to -3
RETICLE	KC-1 MIL	SCR™ - MIL SCR - MOA	MSR2 - MIL SCR2 - MIL	MSR2 - MIL SCR2 - MIL
ILLUMINATION CONTROL	Rotary Dial	Rotary Dial	Rotary Dial	Rotary Dial
ELEVATION ADJUSTMENT KNOB	Resettable Zero	Resettable Zero	Resettable Zero	Resettable Zero
WINDAGE/ELEVATION CLICK VALUE	0.1 mrad	0.1 mrad / 1/4 MOA	0.1 mrad	0.1 mrad
WINDAGE RANGE @100 M	30 MIL	30 MIL/50 MOA	30 MIL	25 MIL
ELEVATION RANGE @100 M	30 MIL	34 mrad / 60 MOA	34 MIL	26 MIL
PARALLAX/FOCUS	Fixed	Side Focus	Side Focus	Side Focus
PARALLAX/FOCUS RANGE	100 yd.	25 yd. to Infinity	25 yd. to Infinity	25 yd. to Infinity
NITROGEN FILLED	Yes	Yes	Yes	Yes
OPERATING TEMP. RANGE	-13° F to +145° F	-13° F to +145° F	-13° F to +145° F	-13° F to +145° F
LENS CAPS	Yes	Yes	Yes	Yes
WATERPROOF/FOGPROOF	Submersible to 33 ft.	Submersible to 33 ft.	Submersible to 33 ft.	Submersible to 33 ft.
BATTERY	CR2450	CR2450	CR2450	CR2450
WARRANTY	Heritage™ Warranty	Heritage™ Warranty	Heritage™ Warranty	Heritage™ Warranty
MSRP PRICE	\$1,954.99	\$2,184.99	\$2,414.99	\$2,874.99

Valid in U.S. and Canada only on items manufactured since 2014. Products manufactured prior to 2014 are covered by the warranty as stated on the original packaging.



We will repair or replace the product at no charge to you. The Steiner Heritage Warranty does not cover loss, theft, deliberate damage or cosmetic damage that does not hinder the performance of the product.

- No warranty card needed.
- No receipt required.
- Warranty is fully transferable to future owners of the product.



STEINER
Nothing Escapes You